## Road Warrior Collection

	MCTERIMANCE
C.C. COMMANNEL C.C. C. MANNEL C.C. C. C. C. PARAMAN M. C.	
ANNAL TELLEDIN AMMETEL BUD ANNALAN YA TAMANAN LUTERA	
HERE CONTRACTOR AND C	
<u>, , , , , , , , , , , , , , , , , , , </u>	
AMANIKATI MANANGKATAT PANUNAN KATATAN ANG ANG ANG ANG ANG ANG ANG ANG ANG A	
	AND THE REPORT OF THE REPORT OF THE
THE DIMENSION OF THE DESIGNMENT OF	

TENACITY - Graphite




VIGOR - Black



VIGOR - Graphite



**TENACITY** - Mineral




GRIT - Zinc

GRIT - Aluminum

FORCE LIGHT - Lead

#### UPHOLSTERY FABRIC

TENACITY - Alloy





VIGOR - Tin

VIGOR - Beige



FORCE DARK - Putty



GRIT - Ore

GRIT - Gravel



FORCE DARK - Platinum

# Road Warrior COLLECTION



 Patterns are covered by a 2 year limited performance warranty. Contact your sales representative for written warranty terms and conditions.

## TECHNICAL INFORMATION

Pattern/Direction Width: 54"	Fiber	Repeat	Backing   Finish (Please inquire about other available finishes to suit your specific needs)	Weight (per yard)	Cleaning Code	Abrasion ASTM 4157 (Double Rubs)	Lightfastness AATCC 16E	Seam Slippage* ASTM-D-4034
Force (Dark & Light) (Up the roll)	100% Polyester	1-3/16"" H 7/16" V	Acrylic with Stain Resistance to meet FMVSS302	13.5 oz.	WS	60,000 (#10 Cotton Duck)	40 hours Class 5	Warp - 53 lbs Fill - 42 lbs
Grit (Up the roll)	100% Polyester	1/8" H 1/8" V	Acrylic with Stain Resistance to meet FMVSS302	11.5 oz.	WS	65,000 (#10 Cotton Duck)	40 hours Class 5	Warp - 74 lbs Fill - 86 lbs
Tenacity (Up the roll)	52% Polyester 48% Polyolefin	1/2" H 5/16" V	Acrylic with Stain Resistance to meet FMVSS302	13.9 oz.	WS	50,000 (#10 Cotton Duck)	40 Hours Class 5	Warp - 80 lbs Fill - 76 lbs
Vigor (Up the roll)	100% Polyester	None	Acrylic with Stain Resistance to meet FMVSS302	12.7 oz.	WS	100,000 (#10 Cotton Duck)	40 Hours Class 5	Warp - 92 lbs Fill - 91 lbs

Cleaning Instructions: WS - For water based stains, use mild detergent foam or upholstery shampoo. For oil based stains, spot clean with a dry cleaning solvent being sure to test area first.

Flame Resistance: California Technical Bulletin 117-2013; NFPA 260; FMVSS302

Fabrics by Absecon Mills, Inc.

#### 02/2020 | For additional cards or memo samples:

### email samples@absecon.com or call 1-877-356-4557



Absecon Mills is focused on being a responsible corporate entity and we are continually striving to find ways to help preserve our environment, increase energy efficiency and reduce waste. Our mode of manufacturing is specifically designed to prevent damage to the environment. Our products are woven using wind power and many are constructed with polypropylene (a by-product of gasoline manufacturing, utilizing post-industrial waste) and recycled polyester, which helps keep post-consumer waste in the material stream and out of landfills. Absecon offers finishes that use ten times

less fluorocarbons than conventional finishes and are SCS Indoor Advantage Gold certified. We participate in a fabric recycling program and work hard to lessen our footprint on the environment. For more information on our green initiatives, please visit www.absecon.com

Colors may vary slightly from dye lot to dye lot.

\*ASTM-D-4034: Seam 12mm from edge using 7 stitches per 25mm (1"), plain lock stitch and a 22 ballpoint needle)





